

Vulcanized fibre or Vulcanized fiber or Vulcanised fibre or fish paper
 --made in china youngman &tianmao

● **Vulcanized fibre series:**

1, Abrasive Vulcanized fibre.

(1) the Abrasive Vulcanized fibre. Main specification contain 0.8 mms; 1.0 mms; 1.2 mms three kinds of.

(2) Dark green Abrasive the Vulcanized fibre. Main specification contain 0.6 mms; 0.7 mms; 0.8 mms; 0.85 mms; 1.0 mms five kinds .

2, Insulate the Vulcanized fibre.

A: the red Vulcanized fibre. Main specification contain

0.5mm 0.7mm 0.8mm 0.85mm 1.0mm 1.2mm 1.5mm 2.0mm 2.5mm 3.0mm, 4.8mm, 6.0mm, 8.0mm, 10mm, 12mm etc...

B: the black insulates the Vulcanized fibre. Main specification contain

0.5mm 0.7mm 0.8mm 0.85mm 1.0mm 1.2mm 1.5mm 2.0mm 2.5mm 3.0mm, 4.8mm, 6.0mm, 8.0mm, 10mm, 12mm etc..

C: gray insulate the Vulcanized fibre. Main specification contain 0.5 mms; 0.8 mms; 1.0 mms; 1.4 mms; 1.6 mms, 2.0 mms six kinds of.

D: the white Vulcanized fibre. Main specification contain 0.25 mms; 0.3 mms; 0.5 mms; 0.8 mms; 1.0 mms; 1.2 mms; 1.4 mms; 1.6 mms, 2.5 mms 3.0mm etc..

E: the brick red Vulcanized fibre. Main specification contain

0.5mm 0.7mm 0.8mm 0.85mm 1.0mm 1.2mm 1.5mm 2.0mm 2.5mm 3.0mm, 4.8mm, 6.0mm, 8.0mm, 10mm, 12mm etc..

3, SLIVE CANS of Vulcanized fibre. The main specification has

780×1250×1.0mm 870×1250×1.0mm 1000×1250×1.0mm 1330×1250×1.0mm 1500×1250×1.0mm 1980×1250×1.0mm 3300×1250×2.0mm etc..

4. welding mask Vulcanized fibre. Main specification contain 1.0 mms; 1.2 mms two kinds of.

5, the shoe industry processes to use the red Vulcanized fibre. Main specification contain 0.4 mms; 0.5 mms two kinds of.

Above five Vulcanized fibre all contain sheet and roll two kinds of packings form.

● **thin insulate the paper series:**

1, thin insulate Vulcanized fibre.

(1) the true colors is thin to Vulcanized fibre. Main specification contain 0.13 mms; 0.18 mms; 0.20 mms; 0.25 mms; 0.30 mms; 0.38 mms; 0.40 mms; 0.45 mms, 0.50 mms nine kinds of.

(2) the red is thin Vulcanized fibre. Main specification contain 0.2 mms; 0.25 mms; 0.30 mms; 0.40 mms; 0.50 mms, 0.80 mms six kinds of.

(3) green thin Vulcanized fibre. Main specification contain 0.10 mms; 0.12 mms; 0.15 mms; 0.17 mms; 0.20 mms; 0.22 mms; 0.25 mms; 0.30 mms; 0.40 mms, 0.50 mms ten kinds of.

Above four specieses containsheet and roll two kinds of packings form.